


Data sheet

Part No.	VRM Turbo LG 2M
Description	rigid conduit, with sectional corrugation, with moulded-on coupler light compression resistance, light impact resistance
Colour	light grey, similar to RAL 7035
Fire Behaviour	non flame propagating
Classification	22211
Compression resistance	> 320 N



Standard: EN 61386-1, EN 61386-21



Compressive strength class	Impact strength	Operating temperature	Bending strength
Light (Class 2)	Light (Class 2)	-5 to +60 °C	Rigid

Art. no.	ED	ID	VPE small/medium/large
084 415	16 mm	13,7 mm	2 m / 74 m / 4144 m
108 881	20 mm	17,4 mm	2 m / 74 m / 2516 m
108 882	25 mm	22,1 mm	2 m / 38 m / 1596 m
084 419	32 mm	28,6 mm	2 m / 38 m / 912 m
084 420	40 mm	35,8 mm	2 m / 14 m / 644 m
084 195	16 mm	13,7 mm	3 m / 111 m / 6216 m
084 196	20 mm	17,4 mm	3 m / 111 m / 3996 m
084 197	25 mm	22,1 mm	3 m / 57 m / 2622 m
084 198	32 mm	28,6 mm	3 m / 57 m / 1368 m
084 199	40 mm	35,8 mm	3 m / 21 m / 966 m
084 200	50 mm	45,1 mm	3 m / 21 m / 630 m

Areas of Recommended Application

Area	
Flush mounted (plaster)	True
Surface mounted	True
Suitable for concrete installation	False
Machine and systems installation	False
Suitable for subsurface installation (screed)	False
Outdoor installation	False
Suitable for installation on wood	True
Hollow wall	True
Underground installation	False

Further technical details

Details	
Halogen free	False
With sleeve	True
Fire retardant version	True
Material	PVC-U